



## PRIMER P7

### *Adhesion and protective spray primer for propellers and Z Drives*

Nautix P7 anticorrosion and adhesion primer is specially formulated to protect propellers and aluminium Z-Drives. P7 improves the adhesion of A7T.speed antifouling but also other paints on GRP surface, bare wood or metal.

The handy spray packing is particularly recommended to paint in difficult areas .

#### PROTECTION

Work in a well ventilated area, wear suitable protective clothing, gloves and eye/face protection. Use in a well-ventilated area, otherwise use mask (EC Standard: AB). Wear imperatively protective goggles and PVC gloves.

#### PREPARATION

Remove or protect anodes before application.

New bare prop or drive: Wash with a detergent and degrease using a cloth soaked in Nautix SD. Sand the surface (paper grade 150) that should be dulled. Rinse with fresh water and let dry. We strongly recommend to apply one coat of Nautix Acralu on metal before application of P7

Maintenance of painted prop: Apply with a clean non fluffy cloth, Degreaser Nautix SD, and dull. Any loose paint must be removed.

#### APPLICATION

Shake and stir thoroughly before use. Do not apply under 10°C.

Spray sparingly from 15 to 20 cm away to give a wet paint layer and avoid dry spray (a rough finish and poor adhesion).

Proceed by repeated brief pressures (approximately 3 seconds), do not spray continuously.

Shake regularly during sprayings.

Recommended number of coats: Adhesion only 1 coat

Cleaner: Nautix D.P. - Clean tools immediately after use.

Recommended wet coat thickness per coat : 80 microns.

#### DRYING TIME

TEMPERATURE	10°C	15°C	20°C	30°C
Hand dry / Overcoating	30 mn	15 mn	10 mn	5 mn
Dry	3 H	2 H	1 H	30 mn

#### TECHN. DATA

Varnish : Vynilic resin — Solvent acetate buthyl, MIBK.

Colour : Grey. Finish : gloss.

Pack size: 300ml spray

Product weight Kg/L: 1,1 +/- 0,05. Volume solids : 19 %. Coverage : 1,5 m<sup>2</sup>/ spray.

Flash point : <=21 °C

#### SAFETY INFO

R 12 Extremely flammable. R 63 Possible risk of harm to the unborn child. R 67 Vapours may cause drowsiness and dizziness. S 16 Keep away from sources of ignition - No smoking. S 2 Keep out of the reach of children. S 23 Do not breathe vapour S 36/37 Wear suitable protective clothing and gloves. S 46 If swallowed, seek medical advice immediately and show this container or label. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. S 13 Keep away from food, drink and animal feedingstuffs. S 24/25 Avoid contact with skin and eyes. S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S 51 Use only in well-ventilated areas. S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. S 64 If swallowed, rinse mouth with water (only if the person is conscious). Emergency phone number : +33 (0)1 45 42 59 59



Nautix – Z.I. des 5 chemins – 56520 Guidel – France

Tel: +33.(0)2.97.65.32.69

Fax: +33.(0)2.97.65.03.54

[info@nautix.com](mailto:info@nautix.com) — [www.nautix.com](http://www.nautix.com)